

Tab. 3 TEVI MECANICE LAMINATE LA CALD conform ASTM A519 continuare tabel

WT	mm	2.41	2.8	3.8	4.8	5.6	7.6	9.5	12.7	15.9	19.1	22.2	25.4	28.6	31.8	34.9	38.1	41.3	44.5	47.6	50.8	54.0	57.2	
	in	0.095	0.110	0.150	0.189	0.220	0.299	0.374	0.500	0.626	0.752	0.874	1.000	1.126	1.252	1.374	1.500	1.626	1.752	1.874	2.000	2.126	2.252	
OD		Lungime maxima [m]																						
mm	in																							
190.5	7.500									8.8	8.5	8.5	8.0	7.5	7.0	7.0	7.0	6.5	6.0	6.0	6.0	6.0	6.0	
193.7	7.626									8.0	8.0	8.0	7.5	7.0	6.5	6.5	6.5	6.0	5.5	5.5	5.5	5.5		
196.9	7.752										8.0	8.0	7.5	7.0	6.5	6.5	6.5	6.0	5.5	5.5	5.5	5.5	5.0	
203.2	8.000										8.0	8.0	7.5	7.0	6.5	6.5	6.5	6.0	5.5	5.5	5.5	5.5	5.0	
209.6	8.252										8.0	8.0	7.5	7.0	6.5	6.5	6.5	6.0	5.5	5.5	5.5	5.5	5.0	
215.9	8.500										8.0	8.0	7.5	7.0	6.5	6.5	6.5	6.0	5.5	5.5	5.5	5.5	5.0	
219.1	8.626											8.0	7.5	7.0	6.5	6.5	6.5	6.0	5.5	5.5	5.5	5.5	5.0	
222.3	8.752											8.0	7.5	7.0	6.5	6.5	6.5	6.0	5.5	5.5	5.5	5.5	5.0	
228.6	9.000											8.0	7.5	7.0	6.5	6.5	6.5	6.0	5.5	5.5	5.5	5.5	5.0	